

What is claimed is:

1. A method of estimating flexure life of a wire harness in which, in the case when a wire bundle, formed by binding a plurality of wires each formed by coating a conductor line with an insulating layer, is allowed to pass through a predetermined protective tube and secured to an external structural member different from said protective tube, the flexure life up to disconnection caused by extending and bending processes of said wire bundle caused by operations of said external structural member is estimated in accordance with a finite element method, comprising:
 - an initial shape determining step of:
 - using an initial shape of a center line of said wire bundle as a substitute for an initial shape of said wire bundle so as to be determined, using an initial shape of a virtual pipe having only a margin dimension of a margin space of said protective tube with respect to said wire bundle as an inner diameter as a substitute for an initial shape of said protective tube so as to be determined, determining an initial shape of a center line of said wire bundle so that the center line of said wire bundle is not limited by two end portions of the virtual pipe, and determining an initial shape of said external structural member;
 - an extending and bending operation analyzing step of: analyzing extending and bending shapes of said wire bundle and said protective tube by virtually estimating operations of said external structural member so as to calculate a change in curvature of said wire bundle;
 - a calculation step of an amount of change in strain for calculating an amount of change in strain of said wire bundle that is a subject for estimation based upon the change in curvature obtained through said extending and bending operation analyzing

2025-10-10 10:00:00

step; and

a collation step of: making a collation on a life estimation curve that is preliminarily set based upon said amount of change in strain calculated in said calculation step of an amount of change in strain so as to predict the flexure life of said
5 wire bundle.

2. The method of estimating flexure life of a wire harness according to claim 1, wherein, in said extending and bending operation analyzing step, a change in curvature of a center line of the wire bundle is used as a substitute for said change in curvature of
10 the wire bundle.

3. The method of estimating flexure life of a wire harness according to claim 1 or 2,

wherein: said life estimation curve represents correlation between the amount of
15 change in strain and said number of bending processes with respect to a single wire that is obtained by actually measuring the number of bending processes up to disconnection by repeatedly bending said single wire with respect to a plurality of amounts of change in strain; and

in said calculation step of an amount of change in strain, a virtual line member,
20 formed by subjecting the respective bending modulus of elasticity of said conductor line and said insulating layer to weighting processes and averaging processes by using ratios of cross-sectional areas, is assumed, and on the assumption that the virtual line member serves as one of said wires, supposing that the bending radius is R_1 in any one of the wires in the furthest bent state at the position that is subjected to the greatest
25 change in bending within an area in which said virtual line member is subjected to

5

1st 10th 2nd 3rd 4th 5th 6th 7th 8th 9th 10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th 25th 26th 27th 28th 29th 30th 31st 32nd 33rd 34th 35th 36th 37th 38th 39th 40th 41st 42nd 43rd 44th 45th 46th 47th 48th 49th 50th 51st 52nd 53rd 54th 55th 56th 57th 58th 59th 60th 61st 62nd 63rd 64th 65th 66th 67th 68th 69th 70th 71st 72nd 73rd 74th 75th 76th 77th 78th 79th 80th 81st 82nd 83rd 84th 85th 86th 87th 88th 89th 90th 91st 92nd 93rd 94th 95th 96th 97th 98th 99th 100th 101st 102nd 103rd 104th 105th 106th 107th 108th 109th 110th 111th 112th 113th 114th 115th 116th 117th 118th 119th 120th 121st 122nd 123rd 124th 125th 126th 127th 128th 129th 130th 131st 132nd 133rd 134th 135th 136th 137th 138th 139th 140th 141st 142nd 143rd 144th 145th 146th 147th 148th 149th 150th 151st 152nd 153rd 154th 155th 156th 157th 158th 159th 160th 161st 162nd 163rd 164th 165th 166th 167th 168th 169th 170th 171st 172nd 173rd 174th 175th 176th 177th 178th 179th 180th 181st 182nd 183rd 184th 185th 186th 187th 188th 189th 190th 191st 192nd 193rd 194th 195th 196th 197th 198th 199th 200th 201st 202nd 203rd 204th 205th 206th 207th 208th 209th 210th 211th 212th 213th 214th 215th 216th 217th 218th 219th 220th 221st 222nd 223rd 224th 225th 226th 227th 228th 229th 230th 231st 232nd 233rd 234th 235th 236th 237th 238th 239th 240th 241st 242nd 243rd 244th 245th 246th 247th 248th 249th 250th 251st 252nd 253rd 254th 255th 256th 257th 258th 259th 260th 261st 262nd 263rd 264th 265th 266th 267th 268th 269th 270th 271st 272nd 273rd 274th 275th 276th 277th 278th 279th 280th 281st 282nd 283rd 284th 285th 286th 287th 288th 289th 290th 291st 292nd 293rd 294th 295th 296th 297th 298th 299th 300th 301st 302nd 303rd 304th 305th 306th 307th 308th 309th 310th 311th 312th 313th 314th 315th 316th 317th 318th 319th 320th 321st 322nd 323rd 324th 325th 326th 327th 328th 329th 330th 331st 332nd 333rd 334th 335th 336th 337th 338th 339th 340th 341st 342nd 343rd 344th 345th 346th 347th 348th 349th 350th 351st 352nd 353rd 354th 355th 356th 357th 358th 359th 360th 361st 362nd 363rd 364th 365th 366th 367th 368th 369th 370th 371st 372nd 373rd 374th 375th 376th 377th 378th 379th 380th 381st 382nd 383rd 384th 385th 386th 387th 388th 389th 390th 391st 392nd 393rd 394th 395th 396th 397th 398th 399th 400th 401st 402nd 403rd 404th 405th 406th 407th 408th 409th 410th 411th 412th 413th 414th 415th 416th 417th 418th 419th 420th 421st 422nd 423rd 424th 425th 426th 427th 428th 429th 430th 431st 432nd 433rd 434th 435th 436th 437th 438th 439th 440th 441st 442nd 443rd 444th 445th 446th 447th 448th 449th 450th 451st 452nd 453rd 454th 455th 456th 457th 458th 459th 460th 461st 462nd 463rd 464th 465th 466th 467th 468th 469th 470th 471st 472nd 473rd 474th 475th 476th 477th 478th 479th 480th 481st 482nd 483rd 484th 485th 486th 487th 488th 489th 490th 491st 492nd 493rd 494th 495th 496th 497th 498th 499th 500th 501st 502nd 503rd 504th 505th 506th 507th 508th 509th 510th 511th 512th 513th 514th 515th 516th 517th 518th 519th 520th 521st 522nd 523rd 524th 525th 526th 527th 528th 529th 530th 531st 532nd 533rd 534th 535th 536th 537th 538th 539th 540th 541st 542nd 543rd 544th 545th 546th 547th 548th 549th 550th 551st 552nd 553rd 554th 555th 556th 557th 558th 559th 560th 561st 562nd 563rd 564th 565th 566th 567th 568th 569th 570th 571st 572nd 573rd 574th 575th 576th 577th 578th 579th 580th 581st 582nd 583rd 584th 585th 586th 587th 588th 589th 590th 591st 592nd 593rd 594th 595th 596th 597th 598th 599th 600th 601st 602nd 603rd 604th 605th 606th 607th 608th 609th 610th 611th 612th 613th 614th 615th 616th 617th 618th 619th 620th 621st 622nd 623rd 624th 625th 626th 627th 628th 629th 630th 631st 632nd 633rd 634th 635th 636th 637th 638th 639th 640th 641st 642nd 643rd 644th 645th 646th 647th 648th 649th 650th 651st 652nd 653rd 654th 655th 656th 657th 658th 659th 660th 661st 662nd 663rd 664th 665th 666th 667th 668th 669th 670th 671st 672nd 673rd 674th 675th 676th 677th 678th 679th 680th 681st 682nd 683rd 684th 685th 686th 687th 688th 689th 690th 691st 692nd 693rd 694th 695th 696th 697th 698th 699th 700th 701st 702nd 703rd 704th 705th 706th 707th 708th 709th 710th 711th 712th 713th 714th 715th 716th 717th 718th 719th 720th 721st 722nd 723rd 724th 725th 726th 727th 728th 729th 730th 731st 732nd 733rd 734th 735th 736th 737th 738th 739th 740th 741st 742nd 743rd 744th 745th 746th 747th 748th 749th 750th 751st 752nd 753rd 754th 755th 756th 757th 758th 759th 760th 761st 762nd 763rd 764th 765th 766th 767th 768th 769th 770th 771st 772nd 773rd 774th 775th 776th 777th 778th 779th 780th 781st 782nd 783rd 784th 785th 786th 787th 788th 789th 790th 791st 792nd 793rd 794th 795th 796th 797th 798th 799th 800th 801st 802nd 803rd 804th 805th 806th 807th 808th 809th 810th 811th 812th 813th 814th 815th 816th 817th 818th 819th 820th 821st 822nd 823rd 824th 825th 826th 827th 828th 829th 830th 831st 832nd 833rd 834th 835th 836th 837th 838th 839th

10

15

20

25

preliminarily obtaining a correlation between an amount of change in strain of a

single wire that is made of the same material as said center conductor line and actual measured values of flexure life;

calculating the greatest amount of change in strain of said center conductor line of a single wire that is assumed to have the greatest change in curvature radius upon
 5 being bent among the wires within the wire bundle serving as a subject for the estimation; and

estimating flexure life of said wire bundle by collating said calculated greatest amount of change in strain of said center conductor line of said wire with said correlation.

10

6. The method of estimating flexure life of a wire harness according to claim 4 or 5,

wherein, in said step of obtaining the correlation, said single wire is repeatedly bent with respect to a plurality of amounts of change in strain to actually measure the
 15 number of bending processes up to disconnection so as to obtain the correlation.

7. The method of estimating flexure life of a wire harness according to any one of claims 4 to 6,

wherein, in said calculation step of the greatest amount of change in strain,
 20 supposing that the center conductor line has a radius of r , that the bending radius is R_1 in said center conductor line in the furthest bent state at the position that is subjected to the greatest change in bending within an area in which said center conductor line is subjected to bending, and that the bending radius is R_2 in said center conductor line in the furthest extended state, said greatest amount of change in strain ($\Delta \epsilon$) is calculated
 25 by the following equation:

$$\Delta \varepsilon = r \cdot (1 / R_1 - 1 / R_2)$$

8. A wire harness designing method, which is used for designing a wire harness
 5 in which a single or a plurality of wires, each formed by coating a conductor line with
 an insulating layer, are bound and placed on a desired application subject, comprising:

an application subject design planning step of planning a design of said
 application subject as a whole;

a wire harness design planning step of planning a design of said wire harness so
 10 as to fit to said application subject; and

a flexure life estimating step of, in the case when said wire harness planned in
 said wire harness design planning step is allowed to pass through a predetermined
 protective tube and secured to an external structural member different from said
 protective tube, estimating flexure life up to disconnection caused by extending and
 15 bending processes of said wire harness in accordance with a finite element method,

said flexure life estimating step comprising:

an initial shape determining step of: using an initial shape of a center line of said
 wire harness as a substitute for an initial shape of said wire harness so as to be
 determined, using an initial shape of a virtual pipe having only a margin dimension of
 20 a margin space of said protective tube with respect to said wire harness as an inner
 diameter as a substitute for an initial shape of said protective tube so as to be
 determined, determining an initial shape of a center line of said wire harness so that the
 center line of said wire harness is not limited by two end portions of the virtual pipe,
 and determining an initial shape of said external structural member;

25 an extending and bending operation analyzing step of: analyzing extending and

a calculation step of an amount of change in strain for calculating an amount of change in strain of said wire harness that is a subject for estimation based upon the change in curvature obtained through said extending and bending operation analyzing step; and

a collation step of: making a collation on a life estimation curve that is preliminarily set based upon said amount of change in strain calculated in said calculation step of an amount of change in strain so as to predict the flexure life of said wire harness.

9. A wire harness designing method, which is used for designing a wire harness in which a single or a plurality of wires, each formed by coating a conductor line with an insulating layer, are bound and placed on a desired application subject, comprising:

an application subject design planning step of planning a design of said application subject as a whole;

a wire harness design planning step of planning a design of said wire harness so as to fit to said application subject; and

20 a flexure life estimating step of estimating flexure life of said wire harness
planned at said wire harness design planning step up to disconnection caused by
extending and bending processes of said wire harness in accordance with a finite
element method,

said flexure life estimating step comprising:

25 an initial shape determining step of determining an initial shape of said wire

harness;

an extending and bending operation analyzing step of: analyzing extending and bending shapes of said wire harness so as to calculate a change in curvature of said wire harness;

5 a calculation step of an amount of change in strain for calculating an amount of change in strain of said wire harness that is a subject for estimation based upon the change in curvature obtained through said extending and bending operation analyzing step; and

10 a collation step of: making a collation on a life estimation curve that is preliminarily set based upon said amount of change in strain calculated in said calculation step of an amount of change in strain so as to predict the flexure life of said wire harness.

15 10. The wire harness designing method according to claim 8 or 9, wherein: said application subject design planning step and said wire harness design planning step are executed by an application subject designing station for designing and planning said application subject, and said flexure life estimating step is executed by a wire manufacturing station for manufacturing said wire harness or said application subject designing station.

20 11. The wire harness designing method according to any one of claims 8 to 10, wherein in said extending and bending operation analyzing step in said flexure life estimating step, said change in curvature of the center line of said wire bundle is used as a substitute for said change in curvature of the wire bundle.

25

20100404

Sub
Re 93040

12. The wire harness designing method according to any one of claims 8 to 11,
 wherein: in said flexure life estimating step, said life estimation curve represents
 correlation between the amount of change in strain and said number of bending
 processes with respect to a single wire that is obtained by actually measuring the
 5 number of bending processes up to disconnection by repeatedly bending said single
 wire with respect to a plurality of amounts of change in strain; and

in said calculation step of an amount of change in strain in said flexure life
 estimating step, a virtual line member, formed by subjecting the respective bending
 modulus of elasticity of said conductor line and said insulating layer to weighting
 10 processes and averaging processes by using ratios of cross-sectional areas, is assumed,
 and on the assumption that the virtual line member serves as one of said wires,
 supposing that the bending radius is R_1 in any one of the wires in the furthest bent state
 at the position that is subjected to the greatest change in bending within an area in
 which said virtual line member is subjected to bending, that the bending radius is R_2 in
 15 the single wire in the furthest extended state, and that the radius of any one of wires
 that has the greatest difference between said value R_1 and said value R_2 is r , said
 amount of change in strain ($\Delta \epsilon$) is calculated by the following equation:

$$\Delta \epsilon = r \cdot (1 / R_1 - 1 / R_2)$$

20

13. The wire harness designing method according to any one of claims 8 to 12,
 wherein in said initial shape determining step of said flexure life estimating step,
 the initial shape of said wire harness is determined based upon at least the diameter of
 said wire harness, the diameter of said wire harness being calculated through a
 25 predetermined arithmetic expression based upon the number and diameters of a

plurality of kinds of wires constituting the wire harness.

14. The wire harness designing method according to claim 8,
 wherein in said initial shape determining step of said flexure life estimating step,
 5 said margin dimension is found by subtracting the diameter of said wire harness from
 the inner diameter of said protective tube, the diameter of said wire harness being
 calculated through a predetermined arithmetic expression based upon the number and
 diameters of a plurality of kinds of wires constituting the wire harness.

- 10 15. The wire harness designing method according to claim 14,
 wherein supposing that the respective wires constituting said wire harness have a
 diameter of d_v , that the number of the respective wires having the diameter d_v is N_v ,
 and that a predetermined coefficient is a_i , the diameter D_x of said wire harness is
 calculated by the following equation:

15 [Equation 2]

$$D_0 = \left\{ \sum_{v=1}^m (d_v^2 \times N_v) \right\}^{1/2}$$

$$D_x = \sum_{i=1}^n (a_i \times D_0^i)$$

16. The program for allowing a computer to execute the respective steps within
 20 the flexure life estimating step in order to realize said flexure life estimating step on
 the computer in a wire harness designing method disclosed in any one of claims 8
 through 15.